

















	SERIES NUMBER	DESCRIPTION & APPLICATIONS	SIZE
MULTIPURPOSE	SERIES 4112  Other colors available: 	QUICK LOCK PUSH-ON HOSE This oil resistant, hose is excellent for use with air tools, to convey water, mild chemicals, and various petroleum products. No clamps or special tools needed. Special braid angle for quick and secure push-on coupling retention. Not recommended for gasoline or diesel fuels. MSHA approved/Non-Conductive. Available in other colors for color-coding. • 300 PSI WP • Non-Conductive • -40°F to +212°F (-40°C to +100°C)	1/4" to 3/4" long length reels
	SERIES 4192 / 4193  Other colors available: 	GENERAL PURPOSE HOSE Economical and versatile general purpose hose. Excellent for air and water service as well as many agricultural chemicals including Lasso® herbicide. EPDM tube and cover resists heat, sunlight, ozone and weathering. Suitable for applications such as oil mist lubricating air lines, but NOT suitable for the transfer of petroleum products. Series 4192 - Red / Series 4193 - Black • 200 to 300 PSI WP • -40°F to +212°F (-40°C to +100°C)	1/4" to 1-1/2" 300' - 500' reels
	SERIES 4194  Other colors available: 	MULTIPURPOSE HOSE A premium quality, multi-purpose hose with excellent flexibility and maximum resistance to air, water, petroleum oils, and lubricating oils. The non-conductive construction has a minimum one megohm resistance per inch at 1000 volts DC. • 250 to 300 PSI WP • -40°F to +212°F (-40°C to +100°C)	1/4" to 1-1/2" 300' - 500' reels
AIR	SERIES 4150 	HEAVY DUTY CONTRACTORS WIRE BRAID AIR HOSE This hose is designed for the most severe service in mines, quarries, and heavy construction. The braided construction offers superior flexing without kinking and is excellent for compressor air application. • 500 to 600 PSI WP • -20°F to +212°F (-29°C to +100°C)	1/2" to 4" 50' & 100' lengths
	SERIES 4160 / 4165 	"AIR DRILL 300" / "ROCK DRILL 400" HD AIR HOSE A light and flexible, yet sufficiently rugged hose, to withstand the abuse and hard service found in mining and construction. It has excellent resistance to abrasion, gouging and weathering. Specially designed for superior flexibility and kink resistance. Series 4160 - 300 PSI WP / Series 4165 - 400 PSI WP • -20°F to +180°F (-29°C to +82°C)	1/2" to 4" 50' & 100' lengths
PETROLEUM	SERIES 4215 / 4245 / 4250 	TANK TRUCK HOSE Series 4215 is a suction and discharge hose designed for the transfer of petroleum products such as oils and refined fuels such as gasoline, diesel, ethanol blends, and other petroleum based products up to 50% aromatic content. The cover is resistant to oils, ozone, and abrasion. Series 4215-150 PSI WP / Series 4245-300 PSI WP / Series 4250-500 PSI WP • -40°F to +180°F (-40°C to +82°C)	1" to 8" 20' & 100' lengths
	SERIES 4230 / 4235 "Xtraflex" 	CORRUGATED TANK TRUCK HOSE An extremely flexible rubber hose used in the transfer gasoline, diesel fuels, oils, ethanol blends, and other petroleum based products up to 50% aromatic content. It is ideal where a super flexible maximum kink resistant fuel transfer hose is needed. Series 4235 - Black Cover • 150 PSI WP • -40°F to +180°F (-40°C to +82°C)	1" to 8" 100' lengths
	SERIES 4240 "Xtraflex" 	"ARCTIC-FLEX" LOW TEMP TANK TRUCK HOSE "Arctic-Flex" is for use in ultra-low temperature operations for transferring gasoline, oil, and other petroleum products. Flexibility maintained down to -65°F (-54°C). It is ideal for tank truck, fuel farm, and oil field service truck use where a cold weather fuel transfer hose is needed. Good up to 50% of aromatics. • 150 PSI WP • -65°F to +180°F (-54°C to +82°C)	2" to 4" 100' lengths
	SERIES 4280 / 4285 "Xtraflex" 	OILFIELD SUCTION - TANK- VAC HOSE An extremely flexible hose designed for oilfield waste pit recovery, tank truck service, including oilfield vacuum truck. Ideal for applications handling crude oil, salt and fresh water, tank bottoms, drilling mud, dilute solutions of hydrochloric acids and sewage transfer. Do not use with refined oils or fuels. Series 4280 - Smooth Cover / Series 4285 - Corrugated Cover • 150 PSI WP • -40°F to +150° (-40°C to +66°C)	2" to 6" 100' lengths



	SERIES NUMBER	DESCRIPTION & APPLICATIONS	SIZE
MATERIAL HANDLING	SERIES 4310 / 4312 	PREMIUM SANDBLAST HOSE Specially compounded tube is formulated to extend service life in sandblasting service. Flexible and kink resistant to reduce operator fatigue. The tube and cover are both static dissipating and the cover is resistant to abrasion and weather. Series 4312 - "Blastmeister" Green Cover • 175 PSI WP • -25°F to +180°F (-32°C to +82°C)	1/2" to 2" 50' & 100' lengths
	SERIES 4340 	DRY CEMENT HANDLING HOSE Recommended for use on bulk transport trucks in discharge service. Abrasion resistant tube handles dry cement, lime, silica, and other abrasive materials. Static dissipating tube and cover. Standard tube thickness of 1/8", 3/16", or 1/4". • 75 PSI WP • -25°F to +180°F (-32°C to +82°C)	4" to 6" 100' lengths
	SERIES 4390 	HOT AIR BLOWER HOSE This hose is specifically designed to convey hot air at 350°F. continuously in the process of loading/unloading dry materials in plants or transport vehicles. The specially formulated EPDM tube and cover offer excellent resistance to heat as well as to weather and ozone. • 75 to 100 PSI WP • -40°F to +350°F (-40°C to +180°C)	2" to 4" 100' lengths
CHEMICAL	SERIES 4410 / 4415 / 4420 "Xtraflex" 	UHMWPE CHEMICAL HOSE The Ultra High Molecular Weight polyethylene tube (UHMWPE) will handle 98% of the most common chemicals without leaching and contaminating the product being conveyed. Series 4410 - Blue Cover / Series 4420 - Black Cover • 150 to 250 PSI WP • -40°F to +212°F (-40°C to +100°C)	3/4" to 6" 100' lengths
	SERIES 4425 	CROSS - LINKED POLYETHYLENE HOSE Cross-link chemical hose solves most chemical handling problems. The tube compound is resistant to 90% of chemicals, solvents, and petroleum products used in industry. The heavy wall resists kinking and crushing for extra safety. • 200 PSI WP • -25°F to +150°F (-32°C to +66°C)	3/4" to 2" 100' lengths
WATER	SERIES 4612 	WATER SUCTION / DISCHARGE HOSE This water suction hose is designed to handle a wide range of applications in industry, construction, and agriculture. The tough, flexible EPDM rubber construction will resist abrasion, weathering and the effects of agricultural herbicides and other mild chemicals. • 150 PSI WP • -20°F to +200°F (-29°C to +93°C)	1" to 12" 20' & 100' lengths
	SERIES 4633 / 4634 	MEDIUM / HEAVY DUTY EPDM DISCHARGE HOSE Series 4633 is medium duty discharge hose and a versatile choice for many water discharge applications. The specially formulated tube and cover is resistant to abrasion, ozone, and weathering. Series 4634 - HD Applications • 150 to 200 PSI WP • -20°F to +180°F (-29°C to +82°C)	1-1/2" to 12" 50' & 100' lengths
FOOD	SERIES 4700 	MULTIPURPOSE FOOD SUCTION & DISCHARGE HOSE A suction and discharge hose designed to handle oily and non-oily food products, liquids, sanitary products, and potable water in a variety of transfer applications. FDA, 3-A, USDA compliant. • 150 PSI WP • -25°F to +230°F (-32°C to +110°C)	1" to 4" 100' lengths
	SERIES 4750 "Xtraflex" 	CORRUGATED MULTIPURPOSE FOOD S/D HOSE A lightweight, highly flexible hose used for the transfer of liquid, dry, oily, or non-oily food products. The specially compounded tube is engineered to handle oily and non-oily products and is resistant to common CIP solutions. FDA, 3-A, USDA compliant. • 150 PSI WP • -25°F to +230°F (-32°C to +110°C)	1-1/2" to 4" 100' lengths